

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-075985

(43)Date of publication of application : 10.03.1992

(51)Int.Cl.

B66B 5/12

B66B 5/18

(21)Application number : 02-191481

(71)Applicant : FUJITSU LTD
FUJITSU VLSI LTD

(22)Date of filing : 18.07.1990


(72)Inventor : KOJIMA TAKAO

(54) ELEVATOR DEVICE

(57)Abstract:

PURPOSE: To prevent an elevator cage from dropping by furnishing a drop preventive mechanism, which prevents drop of elevator cage in the event of severance of rope.

CONSTITUTION: When a rope 12 holding an elevator cage 11 suspendedly is cut, a suspension plate 13 drops in the direction of arrow E by the gravitational force and the action of a spring 16e of a drop preventive mechanism 16. By this drop of suspension plate 13, a detent metal piece 13a of the suspension plate 13 is set off from a detention hole 16c1 provided in a connecting rod 16c of this drop preventive mechanism 16. This connecting rod 16c is moved in the direction of arrow D by another spring 16d. As a result, a rubber plate 16b affixed to the inner surface of a curved plate 16a, which is fixed to the tip of the connecting rod 16c, is touched to the outside surface of a vertical guide shaft 15 by the spring 16d strongly, and a strong friction force is generated between the rubber plate 16b and the outside surface of the vertical guide shaft 15. This prevents the elevator cage 11 from falling.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's]

decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office